HellermannTyton



Article Number: 181-15202

Description: Solid Cable and Wiring Duct, 1.5" x 2", Non-Adhesive, PVC, White, 120 ft/carton

Base Data		
	Local Order Number	181-15202
		SD1.5X2
	Туре	
	Color	White (WH)
	Features and Benefits	 A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement. Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)
	Quantity Per	carton
	Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.
	Technical Description	Non-Adhesive
	Short Description	Solid Cable and Wiring Duct, 1.5" x 2", Non-Adhesive, PVC, White, 120 ft/carton
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.5"
	Width W (Metric)	38.1mm
	Width W2 (Imperial)	1.5"
	Width W2 (Metric)	38.1mm
	Height H (Imperial)	2.07"
	Height H (Metric)	52.6mm
	Mounting Hole Centers (Imperial)	4.0"

181-15202

HellermannTyton

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	CSA
UL Recognized (US)	Yes
Package Quantity (Imperial)	120ft
Package Quantity (Metric)	36.6m
Customs Number(Schedule B)	3925900000
	Material Shortcut Flammability Operating Temperature ROHS Compliant Certification/Specification UL Recognized (US) Package Quantity (Imperial) Package Quantity (Metric)